




# X-FREEZE 4800G

Cowhide, Regular Shoulder Split Leather Driver, Russet Color, Red Fleece Lined, Keystone Thumb



### Key Features & Benefits:

- Economical Split Cowhide Leather provides comfort and durability at a reasonable price.
- Red Fleece lined to keep you warm in cool weather.
- Ergonomic keystone thumb reduces hand fatigue and promotes a wider range of function.
- Shirred elastic back for safety and comfort.
- Still one of the most reliable general purpose gloves in the market.

Applications:		Industries:	Certifications/Ratings:
<ul style="list-style-type: none"> <li>• Steel Work</li> <li>• Masonry</li> <li>• Material Handling</li> <li>• Railroad Work</li> <li>• Light Welding</li> </ul>		<ul style="list-style-type: none"> <li>• Construction</li> <li>• Foundry</li> <li>• Farming</li> <li>• Utilities</li> <li>• Many General Applications</li> </ul>	<p><b>ANSI ISEA-105</b></p> <ul style="list-style-type: none"> <li>• Cut Level-            <b>NR</b></li> <li>• Abrasion Level-      <b>NR</b></li> <li>• Puncture Level-      <b>NR</b></li> </ul> <hr/> <p><b>ANSI ISEA-138</b></p> <ul style="list-style-type: none"> <li>• Impact Level-        <b>NR</b></li> </ul>
Ordering:		Composition	Additional Information
<ul style="list-style-type: none"> <li>• Unit of Sale-        1 DZ</li> <li>• Case pack-         6 DZ</li> <li>• Country of Origin-    Bangladesh</li> <li>• Available Sizes-     S-XL</li> </ul>		<ul style="list-style-type: none"> <li>• 80% Leather, 20% PolyCotton</li> <li>• Cotton Hem</li> </ul>	<p>Wash using warm water and commercial laundry detergent. Water temperature not to exceed 122°F/ 50°C. Air-dry or tumble-dry with no heat</p> <hr/> <p> Warning: Cancer &amp; Reproductive Harm- www.P65Warnings.ca.gov</p>

PACKAGING SPECIFICATIONS

ITEM# 4800G



# X-FREEZE 4800G

Cowhide, Regular Shoulder Split Leather Driver, Russet Color, Red Fleece Lined, Keystone Thumb

## Packaging Dimensions

Item Number	Item Number UPC	Inner UPC	Case UPC	Case L (In)	Case W (In)	Case H (In)	Weight (lbs)
4800GS	196852101092		50196852101097	14.96	9.84	16.54	29.76
4800GM	196852101108		50196852101103	15.35	10.24	16.54	30.86
4800GL	196852101115		50196852101110	15.75	10.63	16.54	31.97
4800GXL	196852101122		50196852101127	16.14	11.02	16.54	33.07



[www.C2VPPE.com](http://www.C2VPPE.com)

