

# TINGLEY

est. 1896

## Class 3 Eclipse™ Jacket

**Stock Number - J44129**

**Compliance Standards:** ANSI/ISEA 107 Type R, Class 3; ASTM F1891; ASTM F2733.



**Garment Detail:** Jackets are set-in sleeve construction with full cut shoulder and 180 degree sleeve-to-body angle. The jacket has a zippered storm fly front with snap closure and an attached hood-in-collar. Sleeve cuffs have hook and loop take-up straps. The jacket has a full vented cape back with fall protection access, 2 front cargo pockets with closure, and adjustable elastic drawcord at waist for added protection.

**Garment Type:** High visibility, liquid proof, flame and arc resistant, and flash fire compliant jacket.

**Reflective Tape:** ANSI/ISEA 107 compliant 2" FR silver glass bead tape.

**Sizes:** S, M, L, XL, 2X, 3X, 4X, 5X

**Color:** Fluorescent Orange-Red.

**Configuration:** Harness tape layout with 1 horizontal band on body, and 2 bands on each sleeve.

**Material:** Fluorescent orange-red material is 10.3 oz./yd<sup>2</sup> FR PVC on non-woven Nomex<sup>®</sup> with Thermo-Grid™ technology.

**Labels/Tags:**

1. Woven label sewn at neck displays Tingley logo and size.
2. Eclipse logo on sleeve cuff take-up.
3. Label sewn into left front hem displays ANSI/ISEA 107, ASTM F1891, NFPA 70E, and ASTM F2733 compliance. Care instructions, fabric composition, lot and date codes are located on the reverse.
4. Label sewn into left front hem displays warning/disclaimer.
5. Name tag is sewn into left front hem.
6. Job Sight FR™ brand and CAT 2 heat transfer label on right pocket closure flap.

**Seam Construction:** All seams are 100% waterproof RF/heat sealed lap construction.

**Closure Type:** Zippered storm fly front with concealed snap closure system.

**Packaging:** Printed polyethylene bag.

**Pockets:** 2 front cargo pockets with flap, and hook and loop closures.

**Other:** Thermal Performance conforms to ASTM F1891, Test Method ASTM F1959.  
Eclipse Orange-Red ARC Rating: 11 cal/cm<sup>2</sup>.  
Flash Fire performance conforms to ASTM F2733, Test Method ASTM F1930.

Dimensions	S	M	L	XL	2X	3X	4X	5X
Chest	46"	50"	54"	58"	62"	66"	70"	74"
Length	29"	30"	31"	31"	32"	32"	32"	33"
Sleeve Length	36"	36"	36.5"	37"	37.5"	38"	38"	40"

**Case Pack:** 12 each

**Case Dimensions/Weight**

S = 15"(L) X 13"(W) X 12"(H) / 25 lbs.

2X = 15"(L) X 13"(W) X 12"(H) / 30 lbs.

M = 15"(L) X 13"(W) X 12"(H) / 26 lbs.

3X = 15"(L) X 13"(W) X 12"(H) / 31 lbs.

L = 15"(L) X 13"(W) X 12"(H) / 27 lbs.

4X = 15"(L) X 13"(W) X 12"(H) / 33 lbs.

XL = 15"(L) X 13"(W) X 12"(H) / 29 lbs.

5X = 15"(L) X 13"(W) X 12"(H) / 35 lbs.

Eclipse™, Thermo-Grid™ and Job Sight FR™ are trademarks of Tingley Rubber Corp.

Nomex<sup>®</sup> is a registered trademark of E. I. du Pont de Nemours and Co.